잉크젯 복합기 무선 연결 ^{By MAC OS}

USB 케이블 연결 후 드라이버가 설치되어 있고 정상 출력이 되는 상태에서 무선 연결 을 진행하는 방법입니다

다운로드 센터 - 유틸리티로 접속합니다

다운로드

드라이버, 유틸리티, 사용자 설명서, 펌웨어, 프로파일을 다운로드 받을 수 있습니다.



제품명 검색				
1차 카테고리	✔ 2차 카테고리	✔ 제품명 선택	▶ 검색	
				제품명 검색
				검색
제품명을 잘 모르실 경우	내가등록한제품	내가 구매한 제품을 등록할 수	수있습니다. <u>제품등록하기</u>	구매하신 제품명을 입력해 주세요.
제품명 자동검색	선택하세요.		▶ 검색	(예 : PIXMA MX700, MX700, 700)
* PC와 연결된 캐논 제품 자동 * 자동 검색 기능 지원 제품:	동 검색을 위한 애플릿을 설켜 복합기, 프린터, 스캐너	이하며, 1~2분 소요됩니다.		

드라이버	유틸리티	사용자 설명서	펌웨어	프로파일	FAQ		
운영체제 선택	!	45개의 데O	터가 있습니다.	유틸리티는 제품검	색과 무관합니다.)		
전체		. log					
Windows 8.1	1 32bit	- <u>log</u>					2015-03-18 🕒 다운로드 자세히 🗸
Windows 8,1	1 64bit						
Windows 8 3	32bit	· <u>Canon IJ</u>	Network Tool V	er. 4.5.0[OS: Ma	<u>d</u>		2015-03-14 🕒 다운로드 달기 🔿
Windows 8 6	54bit						
Windows 7	32bit						
Windows 7 6	54bit	L.	파일명 : mnt *설치 방법*	mac-4_5_0-ea19	_2,dmg (4,9MB)		
Windows Se	rver 2012 64bit		1. 우측의 다운희	로드란의 파일을 클	릭		
Windows Se	rver 2008 32bit		2. 소프트웨어 /	사용권 동의 팝업창	이 나타나면 → 동의함((다운로드) 클릭	
Windows Se	rver 2008 64bit		3. 다운로드 창(4. 다운로드가 9	이 나타나면 열기를 과료된 EXE 파일 실	선택하여 프로그램 다 행 → 안내에 따라 프로	운로드 그램 설치	
110 1 0	2000 02 64	14 C					

다운로드 받은 파일을 실행합니다

	Downloads	Clea
mntmac-4_5_0-ea1 5.1 MB	9_2.dmg	9
RcEngMgr-2 1.3 MB		C
RcEngMgr 1.3 MB		C
2014123109045601.n 16.3 MB	ncpd-m500-11_7_1_0-ea17_2-2.dr	ng 🎯
2014123109045601.m 16.3 MB	cpd-mac-mg3500-11_7_1_0-ea17_2.c	gmg 🦉
googleearth-mac-plug 40.1 MB	gin-intel.dmg	¢
2015년_대회경기일정_강 15 KB	원도골프협회.hwp	C
rs.exe 296 KB		C

설치를 진행합니다 설치 파일을 실행합니다



설치를 진행합니다 Continue(계속)을 클릭합니다

<u> 0 </u>	😺 Install Canon IJ Network Tool
	Welcome to the Canon IJ Network Tool Installer
Introduction	Welcome to the Canon IJ Network Tool Installer. This program guides you through the steps necessary to install Canon IJ Network Tool
License	
Destination Select	
Installation Type	
Installation	
Summary	
	Go Back Continue

설치를 진행합니다 Continue(계속)을 클릭합니다

<u> </u>	🕪 Install Canon IJ Network Tool				
	Software License Agreement				
Introduction	English				
License	END USER LICENSE AGREEMENT				
Destination Select	ATTENTION: PLEASE READ THIS DOCUMENT BEFORE INSTALLING				
Installation Type	THE LICENSED SOFTWARE.				
Installation	This is a license agreement between you and Canon Inc., having its place of business at 30-2 Shimomaruko 3-chome, Ohta-ku, Tokyo 146-8501,				
Summary	Japan ("Canon"), with respect to software programs, its associated electronic or online manuals, and updates thereof if any (collectively, the "Software") and/or text, image, graphic and other creations in digital format, and updates thereof, including those provided via the internet with use of the Software, if any ("Contents Data"), which are provided to you with this End User License Agreement (Software and Contents Data hereinafter shall be referred to individually or collectively as the "Licensed Software").				
	BY INSTALLING THE LICENSED SOFTWARE YOU AGREE TO BE BOUND BY THE TERMS OF THIS AGREEMENT. IF YOU DO NOT AGREE TO THE TERMS OF THIS AGREEMENT, PROMPTLY CLOSE THE INSTALLATION PROGRAM. THE LICENSED SOFTWARE WILL				
	Print Save Go Back Continue				

설치를 진행합니다 Agree(동의)를 클릭합니다

0	0	5) H	😺 Install Canon IJ Network Tool
		To continue ins the software lie	talling the software you must agree to the terms of ense agreement.
	Inti	Click Agree to c	ontinue or click Disagree to cancel the installation and
	Lic	quit the Installe	
	De:		NG
	Ins	Read License	Disagree
	Ins	<u></u>	
	Sumn	hary	Japan ("Canon"), with respect to software programs, its associated electronic or online manuals, and updates thereof if any (collectively, the "Software") and/or text, image, graphic and other creations in digital format, and updates thereof, including those provided via the internet with use of the Software, if any ("Contents Data"), which are provided to you with this End User License Agreement (Software and Contents Data hereinafter shall be referred to individually or collectively as the "Licensed Software"). BY INSTALLING THE LICENSED SOFTWARE YOU AGREE TO BE BOUND BY THE TERMS OF THIS AGREEMENT. IF YOU DO NOT AGREE TO THE TERMS OF THIS AGREEMENT, PROMPTLY CLOSE THE INSTALLATION PROGRAM. THE LICENSED SOFTWARE WILL
		Ļ	Print Save Go Back Continue

설치를 진행합니다 Install(설치)를 클릭합니다

00	😺 Install Canon IJ Network Tool 🦳 🔤
	Standard Install on "Macintosh HD"
 Introduction License Destination Select Installation Type Installation Summary 	This will take 11.7 MB of space on your computer. Click Install to perform a standard installation of this software for all users of this computer. All users of this computer will be able to use this software.
	Go Back Install

설치를 진행합니다 컴퓨터 계정 정보(이름 및 암호)를 입력하고 Install Software(프로그램 설치)를 클릭합니다

 Introduc License Destinat Installati Installati 	Installer is trying to install new software. Type your password to allow this. Username: Password: Cancel Install Software
• Summar	Go Back Continue

설치가 진행됩니다

© <u>©</u> ©	😺 Install Canon IJ Network Tool		(Q) <u>O</u>	🖳 🕹 😜 İnsta	Il Canon IJ Network Tool	
	Installing Canon IJ Network Tool			Installing Ca	anon IJ Network Tool	
 Introduction License Destination Select Installation Type Installation Summary 	Optimizing system for installed s	oftware	 Int Lic De Ins Su 	roduction sense estination Select stallation Type stallation mmary	package scripts	Go Back Continue
	 Introdu License Destina Installa Installa Summa 	Install C Installing Cano I	anon IJ Network Tool	Go Back Continue		

설치가 완료되었습니다. Close(닫기)를 클릭합니다



프로그램을 실행합니다



설정을 진행합니다

Canon IJ Network Tool

Select the connection method between this computer and the printer.

If you plan to use the printer on the network, select [Use the printer on the network], and then click [OK]. Then, configure the printer network settings.

If you do not plan to use the printer on the network, select [Do not use the printer on the network], and then click [OK]. The setup will be complete.

Use the printer on the network

Do not use the printer on the network

Cancel	ОК

(?)





Select the printer to be used on the network, and then click [OK].

If the printer you want to use has not been detected, check the network settings of the printer before clicking [Update].

It may take a few minutes for a printer to be visible on the network after it is turned on. Please wait a while and then click [Update].

OK

설정을 진행합니다

00	Canon IJ Network Tool			
✓ Setup Utilities	실정이라고 되어 있는 것을 유틸리티로 변경을 합니다			
Model (MAC Address) MG3500 series	Name	Type Connected to Canon USB		
Select the printer to be use If the printer you want to u [Update]. It may take a few minutes click [Update]. ?	ed on the network, and then click [OK]. se has not been detected, check the network settin for a printer to be visible on the network after it is tu	Update Configuration gs of the printer before clicking rned on. Please wait a while and then		
		Canon IJ Network	(1001	
		Utilities 🗘		
		Printers:		
		Model (MAC Address) Searching for printers.		Connected to
			Cancel	
			Update	Configuration

If the printer to be used could not be detected, check the network settings before clicking [Update]. After you turn on the printer, it may take a few minutes before the printer can be detected. Wait awhile and then click [Update].

설정을 진행합니다 설치된 프린터를 선택 후 Configuration(구성)을 클릭합니다

0	0 😑 🖸	Canon IJ Network Tool			
	Utilities	0			
	Printers:				
	Model (MAC Address)	Name		Туре	Connected to
	MG3500 series			Canon	USB
				_	
			Update		Configuration
	If the printer to be used cou After you turn on the printer click [Update].	uld not be detected, check the network settings bef r, it may take a few minutes before the printer can b	ore clicking be detected.	(Update Wait av	e]. vhile and then

?

설정을 진행합니다 Search(검색)를 클릭하여 무선 공유기를 검색합니다

Wi	reless LAN Admin Password
Use printer with wireles	s LAN connection
Network Type:	O AirPort Network (Infra)
Network (SSID):	BJNPSETUP Search
Encryption Method:	Do Not Use
	Configuration
TCP/IP Setting:	Get IP address automatically
IP Address:	0.0.0.0
Subnet Mask:	0.0.0.0
	0000

설정을 진행합니다 무선 공유기를 검색하는 중입니다

	Wireless LAN Admin Password	
Searching for wirele	ess routers.	
	Configu	uration
TCP/IP Setting:	Configu Get IP address automatically	uration
TCP/IP Setting: IP Address:	Get IP address automatically 0.0.0.0	uration
TCP/IP Setting: IP Address: Subnet Mask:	Get IP address automatically 0.0.0.0 0.0.0	uration

설정을 진행합니다 사용 중인 무선 공유기 이름을 선택하고 Set(설정)을 클릭합니다

iptime 00:08:9F:7D:0E:B8 iptime 00:08:9F:16:B9:C0 WPA2 826826	vel	Encryption	Wireless Router Name (SSID)	MAC Address
iptime 00:08:9F:16:B9:C0 WPA2 826826	il		iptime	00:08:9F:7D:0E:B8
WPA2 826826	1		iptime	00:08:9F:16:B9:C0
		WPA2	826826	

설정을 진행합니다 TCP/IP Setting(TCP/IP 설정)은 자동으로 맞추면 됩니다

Use printer with wireles Network Type:	AirPort Network (Infra)
Network (SSID):	iptime Search
Encryption Method:	Do Not Use
TCP/IP Setting:	Get IP address automatically
IP Address:	0.0.0.0
Subnet Mask:	0.0.0.0
	0.0.0.0

설정을 진행합니다

0	Wireless LAN Admin Password	
Sending settings to	printer.	
Do not turn off the	printer while the transmission is in progres	s.
	Configu	uration
TCP/IP Setting:	Get IP address automatically	uration
TCP/IP Setting: IP Address:	Get IP address automatically 0.0.00	uration
TCP/IP Setting: IP Address: Subnet Mask:	Get IP address automatically 0.0.0.0 0.0.0.0	uration,

프린터를 추가합니다



프린터를 추가합니다



프린터를 추가합니다

0	Add		
🔒 🌚 🚔	Q Search	Name	A Kind
Default IP Windows	Search	Canon MG3500 series	Boniour Multifunction
		Canon MG3500 series	USB
Name	∧ Kind		
Canon MG3500 series	USB		
4			
			7
Name			AND
Nume.			
Location:			Q Search
Use:	0	Default IP Windows	Search
	Add	Name	^ Kind
		Canon MG3500 series	Bonjour Multifunction
		Canon MG3500 series	Canon IJ Network
		Canon MG3500 series	USB
고리더 ᄎ기르 ㅎ	· · · · · · · · · · · · · · · · · · ·		

프린터 추가를 하게 되면 바로 표시되지는 않습니다 약간의 시간이 지나면 하나씩 추가 가능한 프린터가 표시됩니다. 표시된 것들 중 "Canon IJ Network"를 선택한 후 ADD(추가)를 클릭합니다.

 Name
 ^ Kind

 Canon MG3500 series
 Canon IJ Network

 Canon MG3500 series
 USB

 Vame:
 Canon MG3500

 Name:
 Canon MG3500

 Location:
 Use:

 Use:
 AirPrint

프린터를 추가 합니다 별다른 에러 메시지 없이 완료되는 것이 정상입니다

00	•		Add			
2			C	Search		
Default	-IP I	Windows		Search		
Ne Ce Ce	5	Setting up 'Ca	anon MG3500 WIFI	5		
Cε		Setting up the d	evice			
					Cancel	
	Name:	Canon MG3500	WIFI			
L	ocation:	:				
	Use:	Canon MG3500	series		0	9
					Add	1

테스트 페이지를 출력합니다 Open Print Queue(인쇄 대기열)을 클릭합니다



테스트 페이지를 출력합니다

